

半六角大器拉帽
AHBM, AHBI 系列



Material: steel, stainless steel 302 (inox a2/18-8)
316 (inox a4/18-10), brass, aluminum 5056
Surface finish: steel:
cr3 white/ yellow/ black zinc plated,
cr3 zinc nickel plated, nickel plated.
stainless steel: clean or passivated.
brass: clean
aluminum: clean
材質: 鐵、白鐵302、316、銅、鋁5056。
拉帽之表面處理:
鐵: 三價鉻鍍白/黃/黑鋅、三價鉻鍍鋅鍍、鍍鎳
白鐵: 洗清或鈍化
銅: 洗清
鋁: 洗清

HALF-HEXAGON WITH SMALL FLANGE BERYNUT,
FLAT HEAD, HEX INTERNAL HOLE, OPEN END

AHBM SERIES
AHBI SERIES

THREAD SIZE	PART NO.	HOLE SIZE +0.01/-0.02	D (mm) +0.02/-0.1	L (mm) +/-0.4	A (mm) +/-0.3	H (mm) +0.02/-0.05	GRIP RANGE
M4X0.7	AHEM4	6.35	6.25	10.50	9.50	0.68	0.50-2.50
M5X0.8	AHEM5	7.20	7.00	11.60	9.90	0.68	0.50-3.30
M6X1.0	AHEM6	9.60	9.40	15.40	12.90	0.76	0.50-3.50
M8X1.25	AHEM8	12.70	12.60	18.40	16.50	0.89	0.50-3.80
M10X1.5	AHEM10	12.70	12.60	18.40	16.50	0.89	0.50-3.80
THREAD SIZE	PART NO.	HOLE SIZE +0.004/-0.0	D (inch) +0.0/-0.004	L (inch) +/-0.015	A (inch) +/-0.012	H (inch) +0.006/-0.002	GRIP RANGE
UNC8-32	AHEI 832	250	246	413	374	.027	0.02-0.080
UNC10-24	AHEI 1024	280	276	457	390	.027	0.02-0.130
UNC10-32	AHEI 1032	280	276	457	390	.027	0.02-0.130
UNC14-20	AHEI 420	280	370	606	508	.030	0.027-0.165
UNC5/16-18	AHEI 518	500	496	724	650	.035	0.027-0.150
UNC3/8-16	AHEI 616	500	496	724	650	.035	0.027-0.150

小器拉帽 / 小器直花拉帽

SEM, SAM
SAI 系列

SMALL FLANGE BERYUT, OPEN END

SEM, SAM, SAI SERIES



THREAD SIZE	PART NO.	HOLE SIZE +0.01/-0.0	D (mm) +0.1/-0.0	L (mm) +/-0.4	A (mm) +/-0.3	H (mm) +0.02/-0.05	GRIP RANGE
M3X0.5	SEMS	5.10	5.00	9.00	6.00	0.50	0.50-2.00
M4X0.7	SEMS/ SEM4-K	6.10	6.00	10.00	7.00	0.50	0.50-2.50
M5X0.8	SEMS/ SEM5-K	7.10	7.00	12.00	8.00	0.50	0.50-2.50
M6X1.0	SEMS/ SEM6-K	9.10	9.00	15.00	10.00	0.50	1.00-4.00
M8X1.25	SEMS/ SEM8-K	11.10	11.00	18.00	12.00	0.50	1.00-4.00
M10X1.5	SEMS/ SEM10-K	13.10	13.00	18.00	14.00	0.50	1.00-4.00
THREAD SIZE	PART NO.	HOLE SIZE +0.01/-0.0	D (mm) +0.1/-0.01	L (mm) +/-0.4	A (mm) +/-0.3	H (mm) +0.02/-0.05	GRIP RANGE
M3X0.5	SAMS	4.90	4.80	9.00	5.80	0.50	0.50-2.00
M4X0.7	SAMS/ SAM4-K	6.40	6.30	10.00	7.30	0.50	0.50-2.50
M5X0.8	SAMS/ SAM5-K	7.20	7.10	12.00	8.10	0.50	0.50-2.50
M6X1.0	SAMS/ SAM6-K	9.60	9.50	15.00	10.50	0.50	1.00-4.00
M8X1.25	SAMS/ SAM8-K	10.60	10.50	18.00	11.50	0.50	1.00-4.00
M10X1.5	SAMS/ SAM10-K	12.80	12.70	18.00	13.70	0.50	1.00-4.00
THREAD SIZE	PART NO.	HOLE SIZE +0.004/-0.0	D (mm) +0.0/-0.004	L (mm) +/-0.075	A (mm) +/-0.062	H (mm) +0.006/-0.002	GRIP RANGE
UNC4-40	SAI	.82	.88	355	228	.020	0.02-0.08
UNC6-32	SAH-632/ SAH-632K	253	249	409	289	.020	0.02-0.10
UNC8-32	SAH-832/ SAH-832K	253	249	409	289	.020	0.02-0.10
UNC10-24	SAS-1024/ SAS-1024K	284	280	464	320	.020	0.02-0.10
UNC10-32	SAS-1032/ SAS-1032K	284	280	464	320	.020	0.02-0.10
UNC14-20	SAM/ SAM-K	378	374	575	414	.020	0.04-0.15
UNC5/16-18	SAM/ SAM-K	420	414	630	456	.020	0.04-0.15
UNC3/8-16	SAM/ SAI 10-K	504	500	708	540	.020	0.04-0.15

大器拉帽 / 大器直花拉帽 BEM, BAI 系列

FLAT HEAD BERYUT, OPEN END

BEM, BAI SERIES

THREAD SIZE	PART NO.	HOLE SIZE +0.01/-0.0	D (mm) +0.0/0.1	L (mm) +/-0.3	A (mm) +/-0.3	H (mm) +0.02/-0.05	GRIP RANGE
M3X0.5	BEMS	5.10	5.00	9.80	8.00	0.80	0.50-2.00
M4X0.7	BEM/ BEM4-K	6.10	6.00	11.30	9.00	0.80	0.50-2.50
M5X0.8	BEM/ BEM5-K	7.10	7.00	12.50	10.00	1.00	0.50-2.50
M6X1.0	BEM/ BEM6-K	9.10	9.00	15.00	13.00	1.50	1.00-3.50
M8X1.25	BEM/ BEM8-K	11.10	11.00	18.00	14.50	1.50	1.00-4.00
M10X1.5	BEM/ BEM10-K	13.10	13.00	21.60	16.00	1.60	1.00-4.00
THREAD SIZE	PART NO.	HOLE SIZE +0.004/-0.0	D (mm) +0.0/-0.004	L (mm) +/-0.075	A (mm) +/-0.062	H (mm) +0.006/-0.002	GRIP RANGE
UNC4-40	BAB	.201	.87	386	315	.032	0.02-0.08
UNC8-32	BAH/ BAH-K	240	236	445	354	.032	0.02-0.10
UNC10-24	BAH/ BAH-K	280	276	493	393	.040	0.02-0.10
UNC14-20	BAM/ BAM-K	358	354	630	512	.069	0.04-0.14
UNC5/16-18	BAM/ BAM-K	437	433	709	571	.069	0.04-0.15
UNC3/8-16	BAM/ BAI 10-K	516	512	850	630	.063	0.04-0.15



TOP SCREW METAL CORP.

螺峯金屬工業股份有限公司



小唇直花拉帽 TSSS

Material: steel, stainless steel 302 (inox a2/18-8)
316 (inox a4/18-10), brass, aluminum 5056
Surface finish: steel:
cr3 white/ yellow/ black zinc plated,
cr3 zinc nickel plated, nickel plated.
stainless steel: clean or passivated.
brass: clean
aluminum: clean



SMALL FLANGE, SPLINED BERYUT, OPEN END

TSSS SERIES

THREAD SIZE	PART NO.	HOLE SIZE +01/-00	D (mm) +0.1/-0.0	L (mm) +/-0.4	A (mm) +/-0.3	H (mm) +0.05/-0.05	GRIP RANGE
M4X0.7	TSSS470	6.80	6.75	11.45	7.87	0.48	0.50-2.00
M5X0.8	TSSS580	7.60	7.55	12.85	8.64	0.48	0.50-3.30
M6X1.0	TSSS610	10.00	9.90	15.50	11.50	0.55	0.70-4.00
M8X1.25	TSSS8125	13.50	13.45	18.30	15.11	0.55	0.70-4.00
M10X1.5	TSSS1015	13.50	13.45	18.30	15.11	0.55	0.70-4.00
THREAD SIZE	PART NO.	HOLE SIZE +0.004/-0.00	D (inch) +0.01/-0.004	L (inch) +/-0.015	A (inch) +/-0.012	H (inch) +0.002/-0.002	GRIP RANGE
UNC6-32	TSSS632	.266	.265	.450	.295	.019	0.02-0.08
UNC8-32	TSSS832	.266	.265	.450	.295	.019	0.02-0.08
UNC10-24	TSSS1024	.297	.296	.505	.326	.019	0.02-0.13
UNC10-32	TSSS1032	.297	.296	.505	.326	.019	0.02-0.13
UNC1/4-20	TSSS420	.391	.390	.610	.420	.022	0.027-0.150
UNC5/16-18	TSSS518	.531	.530	.720	.560	.022	0.027-0.150
UNC3/8-16	TSSS616	.531	.530	.720	.560	.022	0.027-0.150



大唇直花拉帽 TSBS

材質：鐵、白鐵302、316、銅、鋁5056。

拉帽之表面處理：
鐵：三價鉻或白/黃/黑鋅、三價鉻鍍鋅、鍍銀
白鐵：洗清或鈍化
銅：洗清
鋁：洗清

LARGE FLANGE, SPLINED BERYUT, OPEN END

TSBS SERIES

THREAD SIZE	PART NO.	HOLE SIZE +01/-00	D (mm) +0.1/-0.0	L (mm) +/-0.4	A (mm) +/-0.3	H (mm) +0.05/-0.05	GRIP RANGE
M4X0.7	TSBS470	6.80	6.75	11.70	9.50	0.76	0.50-2.00
M5X0.8	TSBS580	7.60	7.52	12.07	10.54	0.76	0.50-3.30
M6X1.0	TSBS610	10.00	9.90	14.73	12.70	0.76	0.70-4.00
M8X1.25	TSBS8125	13.50	13.45	17.53	17.00	0.89	0.70-4.00
M10X1.5	TSBS1015	13.50	13.45	17.53	17.00	0.89	0.70-4.00
THREAD SIZE	PART NO.	HOLE SIZE +0.004/-0.00	D (inch) +0.01/-0.004	L (inch) +/-0.015	A (inch) +/-0.012	H (inch) +0.002/-0.002	GRIP RANGE
UNC6-32	TSBS632	.266	.265	.420	.390	.030	0.02-0.08
UNC8-32	TSBS832	.266	.265	.420	.390	.030	0.02-0.08
UNC10-24	TSBS1024	.297	.296	.475	.415	.030	0.02-0.130
UNC10-32	TSBS1032	.297	.296	.475	.415	.030	0.02-0.130
UNC1/4-20	TSBS420	.391	.390	.580	.500	.030	0.027-0.150
UNC5/16-18	TSBS518	.531	.530	.690	.685	.035	0.027-0.150
UNC3/8-16	TSBS616	.531	.530	.690	.685	.035	0.027-0.150

TEL: +886-4-7237159 FAX: +886-4-7246640

E-mail: receipt@topscrow.com.tw

Address: 78, Lane 415, Tay Ho RD., Sec.2,

Ku Yi Li, Changhwa City, Taiwan, R.O.C.

電話: 04-7237159


F傳真: 04-7246640 www.topscrow.com.tw

E-mail: receipt@topscrow.com.tw

地址: 彰化縣彰化市古夷里泰和路二段415巷78號

TOP SCREW METAL CORP.

螺峯金屬工業股份有限公司




半六角大唇拉帽 HBM, HBI 系列

Material: steel, stainless steel 302 (inox a2/18-8)
316 (inox a4/18-10), brass, aluminum 5056
Surface finish: steel:
cr3 white/ yellow/ black zinc plated,
cr3 zinc nickel plated, nickel plated.
stainless steel: clean or passivated.
brass: clean
aluminum: clean

HALF-HEXAGON WITH BIG FLANGE BERYNUT, FLAT HEAD, ROUND INTERNAL HOLE, OPEN END

HBM SERIES HBI SERIES

THREAD SIZE	PART NO.	HOLE SIZE +0.01-0.00	D (mm) +0.01/-0.1	L (mm) +/- 0.4	A (mm) +/- 0.3	H (mm) +0.05/-0.05	GRIP RANGE
M4X0.7	HBM4	6.10	5.90	10.70	9.00	0.90	0.50-2.50
M5X0.8	HBM5	7.10	6.90	13.20	10.00	0.90	0.50-3.00
M6X1.0	HBM6	9.10	8.90	16.00	13.00	1.50	0.50-3.30
M8X1.25	HBM8	11.10	10.90	18.00	16.00	1.50	0.50-3.30
M10X1.5	HBM10	13.10	12.90	21.00	19.00	2.00	0.50-3.50
THREAD SIZE	PART NO.	HOLE SIZE +0.008/-0.00	D (inch) +0.01/-0.004	L (inch) +/- 0.015	A (inch) +/- 0.012	H (inch) +0.006/-0.002	GRIP RANGE
UNC8-32	HBI 832	.240	.232	.421	.354	.035	0.02-0.098
UNC10-24	HBI 1024	.280	.272	.539	.394	.040	0.02-0.118
UNC1/4-20	HBI 420	.358	.350	.630	.512	.059	0.02-0.130
UNC5/16-18	HBI 518	.437	.429	.709	.630	.059	0.02-0.130
UNC3/8-16	HBI 616	.516	.508	.827	.748	.079	0.02-0.138



半六角小唇拉帽 HSM, HSI 系列

材質：鐵、白鐵302、316、鋼、鋁5056。

拉帽之表面處理：
鐵：三價洗清或白/黃/黑鋅、三價鉻鍍鉍鍍、鍍銀
白鐵：洗清或鈍化
鋼：洗清
鋁：洗清

HALF-HEXAGON WITH SMALL FLANGE BERYNUT, HEX FLANGE, HEX INTERNAL HOLE, OPEN END

HSM SERIES HSI SERIES

THREAD SIZE	PART NO.	HOLE SIZE +0.01-0.00	D (mm) +0.01/-0.1	L (mm) +/- 0.4	A (mm) +/- 0.3	H (mm) +0.05/-0.05	GRIP RANGE
M4X0.7	HSM4	6.45	6.35	10.40	7.00	0.40	0.50-2.50
M5X0.8	HSM5	7.20	7.10	11.80	8.00	0.60	0.50-3.00
M6X1.0	HSM6	9.60	9.50	14.60	10.60	0.60	0.50-3.00
M8X1.25	HSM8	10.60	10.50	16.00	11.50	0.60	0.50-3.50
M10X1.5	HSM10	12.70	12.60	18.50	14.50	0.60	0.70-3.80
THREAD SIZE	PART NO.	HOLE SIZE +0.004/-0.00	D (inch) +0.01/-0.004	L (inch) +/- 0.015	A (inch) +/- 0.012	H (inch) +0.006/-0.002	GRIP RANGE
UNC8-32	HSI 832	.254	.250	.409	.376	.016	0.02-0.079
UNC10-24	HSI 1024	.280	.279	.465	.315	.024	0.02-0.118
UNC1/4-20	HSI 420	.378	.374	.575	.417	.024	0.02-0.118
UNC5/16-18	HSI 518	.417	.413	.630	.453	.024	0.02-0.138
UNC3/8-16	HSI 616	.500	.496	.728	.551	.024	0.028-0.150

TEL: +886-4-7237159 FAX: +886-4-7246640

E-mail: receipt@topscrow.com.tw

Address: 78, Lane 415, Tay Ho RD., Sec.2,

Ku Yi Li, Changhwa City, Taiwan, R.O.C.

電話: 04-7237159


F傳真: 04-7246640 www.topscrow.com.tw

E-mail: receipt@topscrow.com.tw

地址: 彰化縣彰化市古奧里泰和路二段415巷78號

TOP SCREW METAL CORP. BERYL®

螺峯金屬工業股份有限公司



全六角大唇拉帽 FHBM, FHBI 系列


Material: steel, stainless steel 302 (inox a2/18-8)
316 (inox a4/18-10), brass, aluminum 5056

Surface finish: steel:
cr3 white/ yellow/ black zinc plated,
cr3 zinc nickel plated, nickel plated.
stainless steel: clean or passivated.
brass: clean
aluminum: clean

FULL-HEXAGON WITH BIG FLANGE BERYNUT, FLAT HEAD, ROUND INTERNAL HOLE, OPENEND

FHBM SERIES FHBI SERIES

THREAD SIZE	PART NO.	HOLE SIZE +0.1/-0.0	D (mm) +0.1/-0.0	L (mm) +1/-0.4	A (mm) +1/-0.3	H (mm) +0.5/-0.05	GRIP RANGE
M4X0.7	FHBM4	6.10	5.90	10.70	9.00	0.90	0.50-2.50
M5X0.8	FHBM5	7.10	6.90	13.70	10.00	0.90	0.50-3.00
M6X1.0	FHBM6	9.10	8.90	16.00	13.00	1.50	0.50-3.30
M8X1.25	FHBM8	11.10	10.90	18.00	16.00	1.50	0.50-3.30
M10X1.5	FHBM10	13.10	12.90	21.00	19.00	2.00	0.50-3.50
THREAD SIZE	PART NO.	HOLE SIZE +0.004/-0.0	D (inch) +0.0/-0.004	L (inch) +1/-0.015	A (inch) +1/-0.012	H (inch) +0.006/-0.002	GRIP RANGE
UNC8-32	FHBI 832	.240	.232	.421	.354	.035	0.02-0.098
UNC10-24	FHBI 1024	.280	.272	.539	.394	.035	0.02-0.118
UNC14-20	FHBI 420	.358	.350	.630	.512	.059	0.02-0.130
UNC5/16-18	FHBI 518	.437	.429	.709	.630	.059	0.02-0.130
UNC3/8-16	FHBI 616	.516	.508	.827	.748	.079	0.02-0.138



全六角小唇拉帽 FHSM, FHSI 系列

材質：鐵、白鐵302、316、銅、鋁5056。

拉帽之表面處理：
鐵：三價鉻鍍或鈍化
白鐵：洗清或鈍化
銅：洗清
鋁：洗清

FULL-HEXAGON WITH SMALL FLANGE BERYNUT, HEX FLANGE, ROUND INTERNAL HOLE, OPENEND

FHSM SERIES FHSI SERIES

THREAD SIZE	PART NO.	HOLE SIZE +0.1/-0.0	D (mm) +0.1/-0.0	L (mm) +1/-0.4	A (mm) +1/-0.3	H (mm) +0.5/-0.05	GRIP RANGE
M4X0.7	FHSM4	6.10	5.90	10.20	6.90	0.50	0.50-2.50
M5X0.8	FHSM5	7.10	6.90	12.00	7.80	0.50	0.50-3.00
M6X1.0	FHSM6	9.10	8.90	15.20	10.00	0.50	0.50-3.30
M8X1.25	FHSM8	10.90	10.90	17.80	12.00	0.60	0.50-3.30
M10X1.5	FHSM10	12.90	12.90	21.00	14.60	0.80	0.50-3.50
THREAD SIZE	PART NO.	HOLE SIZE +0.004/-0.0	D (inch) +0.0/-0.004	L (inch) +1/-0.015	A (inch) +1/-0.012	H (inch) +0.006/-0.002	GRIP RANGE
UNC8-32	FHSI 832	.240	.232	.402	.272	.02	0.02-0.098
UNC10-24	FHSI 1024	.280	.272	.472	.307	.02	0.02-0.118
UNC14-20	FHSI 420	.358	.350	.598	.394	.02	0.02-0.130
UNC5/16-18	FHSI 518	.437	.429	.701	.472	.024	0.02-0.130
UNC3/8-16	FHSI 616	.516	.508	.827	.575	.031	0.02-0.138

TEL: +886-4-7237159 FAX: +886-4-7246640

E-mail: receipt@topscrow.com.tw

Address: 78, Lane 415, Tay Ho RD., Sec. 2,

Ku Yi Li, Changhua City, Taiwan, R.O.C.

電話: 04-7237159

F傳真: 04-7246640 www.topscrow.com.tw

E-mail: receipt@topscrow.com.tw

地址: 彰化縣彰化市古奧里泰和路二段415巷78號